

AMI 200

HOCl System Generator



System Specifications

Data sheet	Automatic
Cell current DC	95 A
Electrical supply	230 VAC 50/60 Hz
Electrical power consumption	1.300 W
Energy to FAC	15, 85 W-h/g
Salt (NaCl) consumption	2,0 ±30% g/l
Salt to FAC	5,0 ±30% g/g
Input water pressure	2,2 bar
Mixed Oxidant Solution production capacity (Anolyte)	205 l/h
ORP (Redox)	850-900 mV
pH	7
FAC concentration	500 ppm
FAC production	82 g/h
Side product NaOH (Catholyte)	3% - pH 13 - ORP -900 mV

Working conditions

Ambient temperature for operation	5-40 °C (24h aver.= 35°C)
Annual average air humidity	≤70% 85% occasionally
Aggressive environment	to be avoided

Cabinet

Dimension LxWxH	1260x300mm H810mm
Cooling medium	air convection

Certification & Warranty

Certification

CE | ECHA Art.95

Warranty

1 year

Key features

Touch screen multicolor PLC

Piping in PTFE (Teflon)- Fittings in PvdF (Kynar)

Automatic start and stop

Process current stabilisation

Dedicated compartments for hydraulics and electronics

Integrated float level switches

Acid sensor

Integrated cell flushing system

Conductivity sensor

Possibility to regulate pH

Micro-switch valves

Double cooled electrodes (Anode and Cathode)

Optional

Remote control capability with Ethernet or Modbus

Remote App for iOS & Android

Integrated pH probe

Integrated ORP (Redox) probe

Full pH adjustment from 3 to 8

Double coating anode (guaranteed 2 years)

Full automated cell flushing system



519.808.7031 | kirkmayercanada.com | info@kirkmayercanada.com
11-1673 Richmond Street, London, ON Canada N6G 2N3



FOLLOW US

