

BMI 10

HOCl System Generator



System Capacities

System Operating Parameters: 12 Active Hours Per Day

*If continuous running time is required to exceed 12 hours per day (max 18 hours per day) consult OEM for special heavy-duty cell upgrade at time of system ordering

System Max Output (Liters) 24/7 Production

500ppm Anolyte/HR	10
500ppm Anolyte/Day	120
500ppm Anolyte/Week	840
500ppm Anolyte/Month	3,600
*Catholyte/HR	.05
*Catholyte/Day	6
*Catholyte/Week	42
*Catholyte/Month	180

*Catholyte is in its concentrated form - dilute 5:1 to reach normal strength

System Max Outputs by Anolyte Type (Liters)

DIN Strength / Day (500 ppm)	120
DIN Strength / Week (500 ppm)	840
DIN Strength / Month (500 ppm)	3,600
No Rinse Sanitizer / Day (150 ppm)	360
No Rinse Sanitizer / Week (150 ppm)	2,520
No Rinse Sanitizer / Month (150 ppm)	10,800
Treated Water / Day (5 ppm)	12,000
Treated Water / Week (5 ppm)	84,000
Treated Water / Month (5 ppm)	360,000

Typical Applications



Transit



Schools



Dental Offices



Hospitals



Veterinarian



Skin Care



Your Leader in On-Site HOCl Hypochlorous Acid Generators

KIRKMAYER is a leading global provider of electrochemically activated solution (ECA) generators, delivering first-rate HOCl systems. Our mission is to design and build electrolytic cells that are more reliable, efficient, and durable than conventional ECA and HOCl generators available on the market today.



FOLLOW US

