

BMI 30

HOCl System Generator



System Capacities

System Operating Parameters: 12 Active Hours Per Day

*If continuous running time is required to exceed 12 hours per day (max 18 hours per day) consult OEM for special heavy-duty cell upgrade at time of system ordering

System Max Output (Liters) 24/7 Production

500ppm Anolyte/HR	30
500ppm Anolyte/Day	360
500ppm Anolyte/Week	2520
500ppm Anolyte/Month	10,800
*Catholyte/HR	1
*Catholyte/Day	12
*Catholyte/Week	84
*Catholyte/Month	360

*Catholyte is in its concentrated form - dilute 5:1 to reach normal strength

System Max Outputs by Anolyte Type (Liters)

DIN Strength / Day (500 ppm)	360
DIN Strength / Week (500 ppm)	2520
DIN Strength / Month (500 ppm)	10,800
No Rinse Sanitizer / Day (150 ppm)	1080
No Rinse Sanitizer / Week (150 ppm)	7,560
No Rinse Sanitizer / Month (150 ppm)	32,400
Treated Water / Day (5 ppm)	36,000
Treated Water / Week (5 ppm)	252,000
Treated Water / Month (5 ppm)	1,080,000

Typical Applications



Transit



Schools



Dental Offices



Hospitals



Veterinarian



Skin Care



Your Leader in On-Site HOCl Hypochlorous Acid Generators

KIRKMAYER is a leading global provider of electrochemically activated solution (ECA) generators, delivering first-rate HOCl systems. Our mission is to design and build electrolytic cells that are more reliable, efficient, and durable than conventional ECA and HOCl generators available on the market today.



FOLLOW US

