

LAMI 050

HOCl System Generator



System Capacities

System Operating Parameters: 12 Active Hours Per Day

*If continuous running time is required to exceed 12 hours per day (max 18 hours per day) consult OEM for special heavy-duty cell upgrade at time of system ordering

System Max Output (Liters) 24/7 Production

500ppm Anolyte/HR	49
500ppm Anolyte/Day	588
500ppm Anolyte/Week	4,116
500ppm Anolyte/Month	17,698
*Catholyte/HR	1
*Catholyte/Day	12
*Catholyte/Week	84
*Catholyte/Month	361

*Catholyte is in its concentrated form - dilute 5:1 to reach normal strength

System Max Outputs by Anolyte Type (Liters)

DIN Strength / Day (500 ppm)	588
DIN Strength / Week (500 ppm)	4,116
DIN Strength / Month (500 ppm)	17,698
No Rinse Sanitizer / Day (150 ppm)	1,940
No Rinse Sanitizer / Week (150 ppm)	13,580
No Rinse Sanitizer / Month (150 ppm)	58,394
Treated Water / Day (5 ppm)	58,800
Treated Water / Week (5 ppm)	411,600
Treated Water / Month (5 ppm)	1,769,880

Typical Applications



Poultry



Dairy



Swine



Cannabis



Veterinarian



Skin Care



Your Leader in On-Site HOCl Hypochlorous Acid Generators

KIRKMAYER is a leading global provider of electrochemically activated solution (ECA) generators, delivering first-rate HOCl systems. Our mission is to design and build electrolytic cells that are more reliable, efficient, and durable than conventional ECA and HOCl generators available on the market today.



FOLLOW US

