

LAMI 100

HOCl System Generator



System Capacities

System Operating Parameters: 12 Active Hours Per Day

*If continuous running time is required to exceed 12 hours per day (max 18 hours per day) consult OEM for special heavy-duty cell upgrade at time of system ordering

System Max Output (Liters) 24/7 Production

500ppm Anolyte/HR	103
500ppm Anolyte/Day	1236
500ppm Anolyte/Week	8652
500ppm Anolyte/Month	37,203
*Catholyte/HR	2
*Catholyte/Day	24
*Catholyte/Week	168
*Catholyte/Month	722

*Catholyte is in its concentrated form - dilute 5:1 to reach normal strength

System Max Outputs by Anolyte Type (Liters)

DIN Strength / Day (500 ppm)	1236
DIN Strength / Week (500 ppm)	8652
DIN Strength / Month (500 ppm)	37,203
No Rinse Sanitizer / Day (150 ppm)	4,078
No Rinse Sanitizer / Week (150 ppm)	28,546
No Rinse Sanitizer / Month (150 ppm)	122,747
Treated Water / Day (5 ppm)	123,600
Treated Water / Week (5 ppm)	865,200
Treated Water / Month (5 ppm)	3,720,360

Typical Applications



Poultry



Dairy



Swine



Cannabis



Veterinarian



Skin Care



Your Leader in On-Site HOCl Hypochlorous Acid Generators

KIRKMAYER is a leading global provider of electrochemically activated solution (ECA) generators, delivering first-rate HOCl systems. Our mission is to design and build electrolytic cells that are more reliable, efficient, and durable than conventional ECA and HOCl generators available on the market today.



FOLLOW US

