

LAMI 300

HOCl System Generator



System Capacities

System Operating Parameters: 12 Active Hours Per Day

*If continuous running time is required to exceed 12 hours per day (max 18 hours per day) consult OEM for special heavy-duty cell upgrade at time of system ordering

System Max Output (Liters) 24/7 Production

500ppm Anolyte/HR	301
500ppm Anolyte/Day	3,612
500ppm Anolyte/Week	25,284
500ppm Anolyte/Month	108,721
*Catholyte/HR	4
*Catholyte/Day	48
*Catholyte/Week	336
*Catholyte/Month	1,444

*Catholyte is in its concentrated form - dilute 5:1 to reach normal strength

System Max Outputs by Anolyte Type (Liters)

DIN Strength / Day (500 ppm)	3,612
DIN Strength / Week (500 ppm)	25,284
DIN Strength / Month (500 ppm)	108,721
No Rinse Sanitizer / Day (150 ppm)	11,919
No Rinse Sanitizer / Week (150 ppm)	83,433
No Rinse Sanitizer / Month (150 ppm)	358,761
Treated Water / Day (5 ppm)	361,200
Treated Water / Week (5 ppm)	2,528,400
Treated Water / Month (5 ppm)	10,872,120

Typical Applications



Poultry



Dairy



Swine



Cannabis



Veterinarian



Skin Care



Your Leader in On-Site HOCl Hypochlorous Acid Generators

KIRKMAYER is a leading global provider of electrochemically activated solution (ECA) generators, delivering first-rate HOCl systems. Our mission is to design and build electrolytic cells that are more reliable, efficient, and durable than conventional ECA and HOCl generators available on the market today.



FOLLOW US

