

LAMI 300

HOCl System Generator



System Specifications

Data sheet	Automatic
Cell current DC	125 A
Electrical supply	230 VAC 50/60 Hz
Electrical power consumption	1.85 kW
Energy to FAC	15,1 W-h/g
Salt (NaCl) consumption	2,5 g/l
Salt to FAC	6,25 g/g
Input water pressure	2,2 bar
Mixed Oxidant Solution production capacity (Anolyte)	305 l/h
ORP (Redox)	850-950 mV
pH	7
FAC concentration	500 ppm
FAC production	122 g/h
Side product NaOH (Catholyte)	3% - pH 13 - ORP -900 mV

Working conditions

Ambient temperature for operation	5-40 °C (24h aver.= 35°C)
Annual average air humidity	≤70% 85% occasionally
Aggressive environment	to be avoided

Cabinet

Dimension LxWxH	1260x300mm H810mm
Cooling medium	air convection

Certification & Warranty

Certification

CE | ECHA Art.95

Warranty

1 year

Key features

Touch screen multicolor PLC

Piping in PTFE (Teflon)

Fittings in PvdF (Kynar)

Automatic start and stop

Process current stabilisation

Dedicated compartments for hydraulics and electronics

Integrated float level switches

Integrated cell flushing system

Possibility to regulate pH

Conductivity sensor

Double cooled electrodes (Anode and Cathode)

Optional

Remote control capability with Ethernet or Modbus

Remote App for iOS & Android

Full pH adjustment from 3 to 8

Double coating anode (guaranteed 2 years)



519.808.7031 | kirkmayercanada.com | info@kirkmayercanada.com
11-1673 Richmond Street, London, ON Canada N6G 2N3



FOLLOW US

