

LAMI 600

HOCl System Generator



System Capacities

System Operating Parameters: 12 Active Hours Per Day

*If continuous running time is required to exceed 12 hours per day (max 18 hours per day) consult OEM for special heavy-duty cell upgrade at time of system ordering

System Max Output (Liters) 24/7 Production

500ppm Anolyte/HR	600
500ppm Anolyte/Day	7,200
500ppm Anolyte/Week	50,400
500ppm Anolyte/Month	216,000
*Catholyte/HR	18
*Catholyte/Day	216
*Catholyte/Week	1,512
*Catholyte/Month	6,480

*Catholyte is in its concentrated form - dilute 5:1 to reach normal strength

System Max Outputs by Anolyte Type (Liters)

DIN Strength / Day (500 ppm)	7,200
DIN Strength / Week (500 ppm)	50,400
DIN Strength / Month (500 ppm)	216,000
No Rinse Sanitizer / Day (150 ppm)	21,600
No Rinse Sanitizer / Week (150 ppm)	151,200
No Rinse Sanitizer / Month (150 ppm)	648,000
Treated Water / Day (5 ppm)	720,000
Treated Water / Week (5 ppm)	5,040,000
Treated Water / Month (5 ppm)	21,600,000

Typical Applications



Poultry



Dairy



Swine



Cannabis



Veterinarian



Skin Care



Your Leader in On-Site HOCl Hypochlorous Acid Generators

KIRKMAYER is a leading global provider of electrochemically activated solution (ECA) generators, delivering first-rate HOCl systems. Our mission is to design and build electrolytic cells that are more reliable, efficient, and durable than conventional ECA and HOCl generators available on the market today.



FOLLOW US

